





Product data sheet

Product category	Gas heater freestanding
Brand	Qlima
Model	FGHX 145
Colour	Black metallic
EAN code	8713508776736

Technical specifications

Heating capacity steps	3 (3500 / 3500 / 3500 W)	
Heating capacity	kW	3,5
Gas connection	3-in-1 Connector	
Energy efficiency class	-	
Consumption (min./max.)	g/h	246 - 246
Autonomy (min./max.)	h	61 - 112
For rooms up to	m ²	16 - 28
	m ³	40 - 70
Gas cylinder capacity (max.)	kg	15
Max. gas bottle dimensions (Ø/h)	mm	325 /
Control	manual	
Dimensions (w x d x h)	mm	280 x 335 x 340
Net. weight	kg	2.5
Warranty	year	2

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.



Package content

Gas heater freestanding, User manual

Accessories (to order)

Description	EAN code

ODS

Oxygen detection safety system



Easy to move



Piëzo ignition

Piezoelectric ignitor: This device takes care that the heater can be ignited easily. No matches or lighters are required to start the heater.

Instant heating: No hours of waiting for the heat to build up, just turn the dial and you have instant radiated heat to warm your hands and feet. At the same time, the gently convection heat will bring a warm glow to the whole room.

Flexible: The gas heater is capable of heating any room at any time. All gas heaters are mobile and can be used to provide extra warmth. For example, in draughty hallways, lounges or keeping you warm in a studyroom.

Efficient and quiet: The gas heater is efficient and quiet. No blowers or fans are required to distribute the heat.

Oxygen depletion sensor (ODS): The gas heater is equipped with oxygen depletion sensors (ODS). These sensors can tell how much oxygen is left in the air. Decrease in oxygen levels will activate the sensor to shut off the gas. This security measure activates long before you would feel the effects of low oxygen levels.

Design: This gas heater is part of a robust range of Qlima products.

Full colour box: The unit is delivered complete (including auxiliary parts) in a full coloured box, displaying applications and operation information in several languages.
