



Product data sheet

Product category	Portable aircos cooling
Brand	Qlima
Model	P 528
Colour	White
EAN code	8713508777337

Technical specifications

EER	W/W	2,6
Energy class		A
Rated current cooling	A	8
Rated power cooling	kW	2,64
Energy consumption - hourly indicative (Qsd/c)	kWh	1
Power supply	V/Hz/Ph	220 - 240~ / 50/60 / 1
Current (max.)	A	4,35
Airflow (high)	m³/h	290
For rooms up to	m³	65 - 90
Dehumidification capacity	l/24 h	26,4
Operating range	°C	18 ~ 35
Thermostatic range	°C	18 ~ 32
Sound pressure noise level at 1 m - high mode (SPL)	dB(A)	55
Sound power level (SWL)	dB	65
Fan speeds	positions	3
Control		electronic / remote control
Included filters	type	Screen
Refrigerant type / GWP / Charge	R/g	R290 / 3 / 245
CO <sub>2</sub> equivalent	tonnes	0,00073
Compressor type		rotary
Dimensions (w x d x h)	mm	410 x 300 x 700
Protection class		IPX0
Net. weight	kg	29
Warranty	year	2



All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content

Portable airconditioner, Remote control, CR2025 battery, Filter, Drainage tube, Hose inlet, Hose outlet, User manual

Accessories (to order)

Description	EAN code





WiFi functionality



Remote control



3 Fan speeds



Cooldown function



Eco-friendly refrigerant




Dehumidifier function



Sleep mode



Timer function



Adjustable airflow



Airfilter function

---

**Wi-Fi:** Powered by Tuya: Smart air conditioning, remotely controlled with Wi-Fi via Tuya App.

---

**Air conditioning:** The unit produces, with relatively high energy, a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air.

---

**Airflow:** Move the air vent direction by adjusting the grill at the front side of the air conditioner and by moving the vertical and horizontal louvers.

---

**Continuous drainage:** In use as dehumidifier it is necessary to connect a continuous drainage tube (not included) to the unit.

---

**Cooldown effect:** The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency, the so called "cool down" effect.

---

**Dehumidification:** The unit can also be used as a dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

---

**Electronic controls:** The unit is equipped with electronic controls.

---

**Exhaust duct:** Hot air and humidity is transported, by an easy to install exhaust duct, outside the room

---

**Fan speed setting:** Select the fan speed: low, medium or high. The display will show the chosen speed.

---

**Filtration system:** This air conditioner is equipped with a screen filter that captures larger particles such as dust. It can be cleaned with a vacuum cleaner and / or lukewarm water.

---

**Full colour box:** The unit is delivered complete with auxiliary parts in a stylish full colour box showing application and operation information in multiple languages.

---

**Wi-Fi control:** Thanks to the free NetHome Plus mobile application, the Smartphone acts as a remote control to start and stop or manage the main functions of the device remotely.

---

**Qlima design:** Futuristic, discreet, high quality and exclusive. The latest technology is also on the remote control and the device control screen.

---

**Refrigerant gas R290:** Natural gas with high energy efficiency. Environmentally friendly, R290 gas has a neutral impact on the ozone layer.

---

**Temperature indication:** When the appliance is operating, the room temperature is displayed on the screen. It can vary between 18 ° C and 35 ° C. NOTE: The device adapts to the conditions of the room.

---

**Timer:** Operating time to be set to 24 hours. The unit switches off or on automatically when the set time has run down.

---

**Window adapter kit:** The adapter at the end of the exhaust pipe fits on an insulating support which is placed between the window and its post.

---