Fiorina 90-2 S-Line

Pellet stove









W x D x H = 53 x 53 x 102 cm



Gross weight 100 kg

Product data sheet

| Product category | Pellet stoves |
|------------------|---------------------|
| Brand | Qlima |
| Model | Fiorina 90-2 S-Line |
| Colour | Red |
| EAN code | 8713508762579 |

Technical specifications

| Technical specifications | | |
|--|---------|-------------------------------|
| Heating input - nominal | kW | 9,7 |
| Heating capacity (min./max.) | kW | 3 - 8,7 |
| Consumption pellets (min./max.) | kg/h | 0,7 - 2 |
| Ductable | | not ductable |
| Hermetically sealed | | No |
| Power consumption at start/heating | W | 300 / 115 |
| For rooms up to | m³ | 80 - 240 |
| | m² | 32 - 96 |
| Emission dust (nominal at 13% O ₂) | mg/m³ | 12 |
| Emission NOx at 13% O2 (nominal/reduced) | mg/m³ | 121 - 120 |
| Emission OGC at 13% O2 (nominal/reduced) | mg/m³ | 2 - 7 |
| Emission CO at 13% O ₂ (nom. / reduced) | mg/m³ | 50 - 187,5 |
| Control | | thermostatic / remote control |
| Power supply | V/Hz/Ph | 220 - 240~ / 50 / 1 |
| Dimensions (w x d x h) | mm | 470 x 476 x 996 |
| Net. weight | kg | 91 |
| Hopper capacity | kg | 13 |
| Sound pressure level | dB(A) | 39 - 52 |
| Exhaust location | | back |
| Diameter exhaust | mm | 80 |
| Flue gas temperature (nom. / reduced) | °C | 145,9 / 84,4 |
| Can be used in combined flue system | | No |
| Efficiency (nom. / reduced) | % | 89,5 / 91,3 |
| Autonomy (min./max.) | h | 6,5 - 18 |
| Fuel compatibility | | 6x30mm pellet |
| EEI / Energy efficiency class | | 126 / A+ |
| Warranty | year | 2 |
| All data is a second in a second as a filter | | - 'C' - d - t d d t th - t' C |

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content

Pellet stove, Remote control, Installation manual, User manual



Accessories (to order)

| Description | EAN code |
|---|-------------|
| Remote control Fiorina/Delfina/Rosada/Diandra [8713508766577] | - |



Energy saving mode



5 Fans speeds



Daytimer



Backside flue gas outlet



Adjustable thermostat



Remote control

Automatic regulating function: An integrated room temperature sensor activates the heater according to the programmed temperature. The hot air ignition system starts and switches off once the desired temperature has been reached. This automatic function can be programmed twice a day for the whole week.

Ease of operation: The stove has a system, which turns on the heater automatically once activated. The capacity is regulated with a computer feedback system and an integrated room temperature sensor to achieve the desired room temperature. And then the heater will automatically reduce its heat output to low, the heater will not turn off.

Comfortable to use: Easy, clean and safe. Pellet fuel has a high efficiency rating and is convenient and easy to use.

2 program-week timer: This week timer enables you to set 2 heating periods over the course of the day. These settings are identical for every day of the week. The time tables must be within the same day (0:00-24.00h). Example: time slot 1=08.00-10.00h, time slot 2=16.00-18.00h. For each individual day of the week you now select your preference: no slots or slot 1 or slot 2 or both slots.

Efficiency: With its objectively tested efficiency this stove is amongst the highest efficient machines available in the market.

Continuous operation: This pellet stove has a hopper container of 13 kg, which allows for 18 hours of burning time.

Convenience: Pellets are easy to use, and they come in bags. This fuel offers maximum convenience, while at the same time providing a high efficiency rating.

Safety: Thanks to multiple safety systems, the pellet heater reacts automatically to abnormal conditions in operation or excess flue pressure with an immediate shutdown.

Easy maintenance: Basic maintenance of the pellet stove is easy to do. The daily cleaning of the burning pot is very important for optimal performance. In case of professional service, all the stove components are easily accessible and is rarely detached from the chimney.

Flame pattern: The pellet heaters has a large window revealing an attractive flame pattern, inciting a cosy atmosphere in the room.

Heat exchanger: A high efficiency is achieved due to a sophisticated heat exchanger in combination with modern software control technologies for optimized hot air flow.

Save mode: The stove shuts down automatically when the room temperature is 2°C above the set temperature and restarts when 2°C below the set temperature. This system enables to save energy.

Made in Italy: This heater has been produced in Italy according to the EN 14785:2006 standard.

An innovative design: This Italian designed pellet stove is elegant and is high capacity and efficiency.

Design: A timeless design, a pellet stove is an elegant addition to your home.

Large window: The big window gives a nice view on the fire inside the fire chamber and realy enhances the atmosphere created by this pellet stove.