TP 3020

Portable airconditioner









W x D x H = 36 x 38 x 83 cm



Gross weight 25 kg

Product data sheet

Product category	Portable aircos cooling
Brand	Tectro
Model	TP 3020
Colour	White
EAN code	8713508786315

Technical specifications

r commodi opcomoditorio		
EER	W/W	2,6
Energy class		A
Rated current cooling	Α	9
Rated power cooling	kW	2,05
Energy consumption - hourly indicative (Qsd/c)	kWh	0,789
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1
Current (max.)	Α	5
Airflow (high)	m³/h	285
For rooms up to	m³	50 - 65
Dehumidification capacity	l/24 h	42
Operating range	°C	17 ~ 35
Thermostatic range	°C	17~30
Sound pressure noise level at 1 m - high mode (SPL)	dB(A)	51,9
Sound power level (SWL)	dB	62
Fan speeds	positions	2
Control		electronic / remote control
Included filters	type	Screen
Refrigerant type / GWP / Charge	R/g	R290 / 3 / 140
CO₂ equivalent	tonnes	0,00042
Compressor type		rotary
Dimensions (w x d x h)	mm	325 x 329 x 647
Protection class		IPX0
Net. weight	kg	22
Warranty	year	2

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content

Portable airconditioner, Remote control, AAA battery (2x), Filter, Drainage tube, Hose inlet, Hose outlet, User manual

Accessories (to order)

Description EAN		code
	Description	



TP 3020

Portable airconditioner



2 year guarantee



Timer function



R290

Eco-friendly refrigerant R290



Cooldown function



Dehumidifier function



Remote control



Sleep mode

Air conditioning: The unit produces, with relatively high energy, a pleasant and refreshing high capacity cool airflow. Unhealthy particles are captured by the air filters. Performance is optimal when the entering of warm outside air.

Electronic controls: The unit is equipped with electronic controls.

Remote control: This unit can be operated with an easy to handle remote control.

Temperature indication: When the appliance is operating, the room temperature is displayed on the screen. It can vary between 17 ° C and 35 ° C. NOTE: The device adapts to the conditions of the room.

2 Fan speed setting: Select the fan speed: low or high. The display will show the chosen speed.

Timer: Operating time to be set to 24 hours. The unit switches off or on automatically when the set time has run down.

Washable screen filter: Retains larger particles of air dust.

Cooldown effect: The unit removes humidity by condensation. The condensate cools the condenser and is removed by the hot air discharge. This will increase the energy efficiency, the so called "cool down" effect.

Dehumidification: The unit can also be used as a dehumidifier only. In that case the exhaust hose is not connected and warm air returns in the room.

Continuous drainage: In use as dehumidifier it is necessary to connect a continuous drainage tube (not inlcuded) to the unit.

Exhaust duct: Hot air and humidity is transported, by an easy to install exhaust duct, outside the room

Refrigerant gas R290: Natural gas with high energy efficiency. Environmentally friendly, R290 gas has a neutral impact on the ozone layer.