SM 17 MULTI

Multi split unit air conditioner



Product data sheet

Product category	uct category Wall mounted multi-	
Brand		Qlima
Model		SM 17 MULTI
Colour		White
EAN code		8713508798912
EAN indoor unit	S 1709 / S 1712 (2 / 1)	8713508798882 / 8713508798899
EAN outdoor unit	SM 17 MULTI (1)	8713508798936

Technical specifications		Cooling	Heating
SEER/SCOP	W/W	6,1	3,9
Energy efficiency class average season		A++	А
PdesignC / PdesignH	kW	7,8	5,7
Capacities cooling / heating (min./nom./max.)		2,50 / 7,90 / 8,20	2,00 / 7,90 / 8,20
Power consumption (nom.)	kW	2,445	2,1
Indicative annual energy consumption during season (Qce / Qhe)	kWh/a	448	2046
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1	
Current (max.)	Α	18	
Airflow (low/mid/high)	m³/h	450 / 490 / 570	
For rooms up to indoor unit \$ 1709 / \$ 1712 (2 / 1)	m³	60 - 85 / 80 - 100	
Dehumidification capacity	l/24 h	24 / 28,8	
Operating range - indoor unit	°C	16 ~ 32	0~30
Operating range - outdoor unit	°C	-15 [~] 50	-15 [~] 24
Thermostatic range	°C	16~30	
Sound pressure level indoor \$ 1709 / \$ 1712 (2 / 1) unit at 1m (SPL)	dB(A)	37 / 40,5	
Sound pressure level - outdoor unit at 1m (SPL)	dB(A)	58	
Fan speeds	positions	3	
Control		electronic / remote control	
Air filter	type	Screen	
Refrigerant type / GWP / Charge	R/g	R32 / 675 / 1850	
CO₂ equivalent	tonnes	1,24	
Max. length refr. pipe between in- / outdoor unit	m	15	
Max. diff. in height between in-/outdoor unit	m	10	
Diameter gas connection	Ø mm/inch	9,52 (3/8)	
Diameter liquid connection	Ø mm/inch	6,35 (1/4)	
Dimensions indoor unit (w x d S 1709 / S 1712 (2 / 1) x h)	mm	726 x 210 x 291 / 802 x 295 x 200	
Dimensions outdoor unit (w x d x h)	mm	890 x 342 x 673	
Compressor		twin rotary	
Protection class - indoor/outdoor		IPX0	/ IPX4
Net. weight - indoor unit \$ 1709 / \$ 1712 (2 / 1)	kg	7,7 / 8,2	
Net. weight - outdoor unit	kg	48	
Warranty	year	:	2
Warranty compressor	year		1

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.



Outdoor unit, Indoor unit (3x), Remote control (3x), Remote control noider (3x), Drainage tube 4m (3x), User manual, Installation manual



Description EAN code







WxDxH=

in: 79 x 27 x 37.5 cm in: 87.5 x 28.5 x 38 cm

out: 103 x 43.8 x 75 cm



Gross weight

in: 9.9 kg in: 10.9kg out: 51.8 kg



SM 17 MULTI

Multi split unit air conditioner



Multi-split (1:3)



Cooling, heating & dehumidifying



Inverter techology



K3Z

Eco-friendly refrigerant R32



Remote control with display included



Timer function



Sleep mode

Multi-split: Flexible matching of up to three indoor units with only 1 outdoor unit. The indoor units can run independently from each other as long as they're all-in heating or cooling mode.

Cooling + dehumidifying + heating (heat pump): The air conditioning is a complete year-round air treatment system. It heats and cools in an efficient way and can also be used as a dehumidifier.

Inverter technology: The DC Inverter air conditioner uses its maximum power to get to the set temperature when the appliance is turned on. Once the tempeature is reached, the unit continuously adjusts the compressor speed to maintain the set temperature.

Environment friendly refrigerant R32: The most preferred and environmental friendly refrigerant R32 is used in the air conditioner

Remote control with LCD screen: The air conditioner can be operated by the remote control up to a distance of approx. 8 metres.

Timer: Timer function can be set between 30 minutes and 24 hours (Timer On or Timer Off).

Sleep Mode: The air conditioner increases (cooling) or decreases (heating) automatically the set temperature with 1°C per hour (first two hours) and then maintain the temperature (next five hours). After 7 hours, the unit will stop automatically. In this mode the unit works silently and saves energy at the same