

R 3224 X

Paraffin wick heater



Product data sheet

Product category	Paraffin wick heaters
Brand	Qlima
Model	R 3224 X
Colour	Black
EAN code	8713508785295

Technical specifications

Burner type		Single Burner
Capacity heating	kW	2,40
For rooms up to	m ²	16 - 34
	m ³	40 - 85
Consumption (max.)	l/h	0,25
	g/h	200
Capacity tank	l	4,2
Autonomy (min./max.)	h	16,8 - 16,8
Batteries required		Yes
Batteries included		No
Dimensions (w x d x h)	mm	455 x 295 x 495
Net. weight	kg	9
Warranty	year	4

Safety features Tip-over switch - Safety stop - Overheat protection - Safe top

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.


Package content


Paraffin wick heater, User manual

Accessories (to order)

Description	EAN code

CE ^{guarantee} **4** YEARS

 20 ft = 336
40 ft = 687
40 HQ = 855

 **W x D x H =**
48 x 32 x 52 cm

 **Gross weight**
10 kg

Qlima

guarantee

4

YEARS

4 Year guarantee



Safe top



Fuel filter included



Removable fuel tank



Safety stop



Tip-over safety switch



Easy to move

Automatic tip-over switch: The heater will be shut off automatically when the heater is knocked over.

Battery cover:

This heater is equipped with a cover for the batteries.

High efficiency: This heater has a 99.99% heat efficiency with infrared radiation heating.

No installation: This heater can be installed without wires and without exhaust pipes. This makes it a very convenient heating source.

Safe top: The temperature of the top plate is kept relatively low for improved safety.

Safety stop: This heater is equipped with a shut-off safety switch. By pressing this switch the heater will be shut off immediately.

Tank removal safety system:

This heater is equipped with a safety system that will shut off the heater in the event that the fuel tanks is removed.

Wick-stop: The wick stop mechanism of this heater limits the flame height adjustment. This ensures a clean combustion.

Fuel filter:

Protects the burner system.
