
SM 23 379

Clima Clima





W x D x H =

in: 79 x 27 x 37.5 cm in: 87.5 x 28.5 x 38 cm out: 103 x 43.8 x 75 cm

g

Gross weight in: 9.9 kg

	3.3 Kg
in:	10.9kg
out:	51.8 kg



Multi split unit air conditioner

Product data sheet

Product category		Wall mounted multi-split aircos
Brand		Qlima
Model		SM 23 379
Colour		White
EAN code		8713508794945
EAN indoor unit	S 2326 / S 2335 (2 / 1)	8713508794822 / 8713508794839
EAN outdoor unit	SM 23 379 (1)	8713508794891

Technical specifications		Cooling	Heating	
SEER/SCOP	W/W	6,1	3,9	
Energy efficiency class average season		A++	А	
PdesignC / PdesignH	kW	7,8	5,7	
Capacities cooling / heating (min./nom./max.)		2,50 / 7,90 / 8,20	2,00 / 7,90 / 8,20	
Power consumption (nom.)	kW	2,455	2,1	
ndicative annual energy consumption during season (Qce / Qhe)	kWh/a	448	2046	
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1		
Current (max.)	А	18		
Airflow (low/mid/high)	m³/h	450 / 490 / 570		
For rooms up to indoor unit \$ 2326 / \$ 2335 (2 / 1)	m³	60 - 85 / 80 - 100		
Dehumidification capacity	l/24 h	24 / 28,8		
Operating range - indoor unit	°C	16 ~ 32	0~30	
Operating range - outdoor unit	°C	-15 ~ 50	-15 [~] 24	
Thermostatic range	°C	16~30		
Sound pressure level indoor S 2326 / S 2335 (2 / 1) unit at 1m (SPL)	dB(A)	37 / 40,5		
Sound pressure level - outdoor unit at 1m (SPL)	dB(A)	58		
Fan speeds	positions	3		
Control		electronic / remote control		
Air filter	type	Screen		
Refrigerant type / GWP / Charge	R/g	R32 / 675 / 1850		
CO ₂ equivalent	tonnes	1,24		
Max. length refr. pipe between in- / outdoor unit	m	15		
Max. diff. in height between in- / outdoor unit	m	10		
Diameter gas connection	Ø mm/inch	9,52 (3/8)		
Diameter liquid connection	Ø mm/inch	6,35 (1/4)		
Dimensions indoor unit (w x d S 2326 / S 2335 (2 / 1) x h)	mm	726 x 210 x 291 / 802 x 295 x 200		
Dimensions outdoor unit (w x d x h)	mm	890 x 342 x 673		
Compressor		twin rotary		
Protection class - indoor/outdoor		IPX0	IPX0 / IPX4	
Net. weight - indoor unit \$ 2326 / \$ 2335 (2 / 1)	kg	7,7 / 8,2		
Net. weight - outdoor unit	kg	48		
Warranty	year 2			
Warranty compressor	year	4		

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content

Outdoor unit, Indoor unit (3x), Remote control (3x), Remote control holder (3x), Drainage tube 4m (3x), User manual, Installation manual

Accessories (to order)

Description

EAN code

SM 23 379



Multi-split (1:3)



WiFi functionality

*

Cooling, heating & dehumidifying

Inverter techology



Eco-friendly refrigerant R32



Remote control with display included



Timer function



Sleep mode

Multi split unit air conditioner

Multi-split: Flexible matching of up to three indoor units with only 1 outdoor unit. The indoor units can run independently from each other as long as they're all-in heating or cooling mode.

Wireless smart control: The air conditioner is equipped with Wi-FI for extra comfort and to save energy. With the smart app you can start, stop or operate the main functions of the air conditioner remotely.

Cooling + dehumidifying + heating (heat pump): The air conditioning is a complete year-round air treatment system. It heats and cools in an efficient way and can also be used as a dehumidifier.

Inverter technology: The DC Inverter air conditioner uses its maximum power to get to the set temperature when the appliance is turned on. Once the temperature is reached, the unit continuously adjusts the compressor speed to maintain the set temperature.

Environment friendly refrigerant R32: The most preferred and environmental friendly refrigerant R32 is used in the air conditioner.

Remote control with LCD screen: The air conditioner can be operated by the remote control up to a distance of approx. 8 metres.

Timer: Timer function can be set between 30 minutes and 24 hours (Timer On or Timer Off).

Sleep Mode: The air conditioner increases (cooling) or decreases (heating) automatically the set temperature with 1°C per hour (first two hours) and then maintain the temperature (next five hours). After 7 hours, the unit will stop automatically. In this mode the unit works silently and saves energy at the same time.