EPH 1200 LCD

Electric panel heater



Product data sheet


Product category	Fan heaters
Brand	Qlima
Model	EPH 1200 LCD
Colour	White
EAN code	8713508745640

Technical specifications

Heating capacity steps		1 (1200) W
Heating capacity	kW	1,2
Suitable for space (max.)	m³	50
Current (nom.)	А	5,22
Power supply	V/Hz/Ph	220 - 240~ / 50 / 1
Protection class		IPX4
Control		manual
Dimensions (w x d x h)	mm	660 x 75 x 400
Net. weight	kg	4.5
Warranty	year	2

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.







W x D x H = 70 x 12 x 45 cm



Gross weight 5.5 kg

Package content

Electric panel heater

Accessories (to order)

Description EAN code



EPH 1200 LCD

Electric panel heater





Built-in display



Daytımer



Frost protection



Easy to operate



Open window function

Adjustable thermostat: Control the required room temperature with ease by using the adjustable thermostat.

Overheat protection: Safety of the system is protected against overheating by an auto-shut off function.

Design: This electric panel heater is part of a robust range of Qlima products.

Full colour box: The unit is delivered completely with auxiliary parts in a full coloured box showing applications and operation information in several languages.

Timer: Timer can be set up to 24 hours. The unit switches off or on automatically when the set time is reached.

Wall mounted: The electric panel heater can be installed with ease against the wall.

Digital room temperature setting: The electric panel heater has a digital temperature control, to adjust the heating capacity according to the desired room temperature.

Automatic room temperature setting: Allows the user to set a set-point temperature with the automatic control, which will be maintained whenever the timer is timed to be on.

Anti-frost function: This protects the unit against temperature as low as -5°C.

Auto-restart function: The electric panel heater switches on automatically after a power failure.